

## E-Z-GO® EXPRESS™ S6

## **EXPLORE A NEW PATH.**

Every day is an opportunity to experience something new. The Express S6 is built to help you enjoy your days in style and keep you ready for whatever lies ahead. So grab your friends and family and hop into the Express S6 to see where the day can take you.

## STANDARD FEATURES

- ▶ 18-in street tires
- ▶ Polished diamond-pattern spoke wheels
- ▶ Two-tone seats
- ▶ Front brush guard
- ▶ Headlights, taillights & brake lights
- ► Fold-down cargo deck
- ► Cupholders
- ► Dashboard storage pockets
- ► Low oil indicator (gas only)
- ► Fuel gauge (gas only)
- State-of-charge meter (electric only)



|                                  | ELECTRIC  | GAS  |
|----------------------------------|---|--|
| <b>DIMENSIONS</b> Overall Length | 141.5 in (359 cm)   | 141.5 in (359 cm)  |
| Overall Width                    | 48.5 in (123 cm)  | 48.5 in (123 cm)   |
| Overall Height (w/o roof)        | 49.5 in (126 cm)  | 51.5 in (131 cm)   |
| Overall Height (w/ roof)         | 74.5 in (189 cm)  | 76.5 in (194 cm)   |
| Wheel Base                       | 95.5 in (243 cm)  | 93.5 in (237 cm)   |
| Front Wheel Track                | 38.5 in (98 cm)   | 38.5 in (98 cm)  |
| Rear Wheel Track                 | 39.0 in (99 cm)   | 39.0 in (99 cm)  |
| round Clearance @ Differential   | 5.5 in (14 cm)  | 4.5 in (11 cm)   |
| <b>POWER</b> Power Source        | 48 Volt DC  | 4-Cycle 24.5 cu in (401 cc) Low-Emissions  |
| Valve Train                      | N/A   | Single Cylinder OHV  |
| Motor Type                       | Shunt Wound   | N/A  |
| Horsepower (kW)                  | N/A   | 13.5 hp (10.1 kW) Exceeds SAE J1940 Std  |
| Electrical System                | 48 Volt   | Starter/Generator — Solid State Regulator  |
| Batteries (qty/type)             | Eight, 6 Volt Deep Cycle  | One, 12 Volt Maintenance Free  |
| Key or Pedal Start               | Pedal   | Pedal  |
| Air Cleaner                      | N/A   | Replaceable Dry Cartridge  |
| Lubrication                      | N/A   | Pressurized Oil System   |
| Oil Filter                       | N/A   | Spin-On  |
| Cooling System                   | N/A   | Air Cooled   |
| Fuel Capacity                    | N/A   | 5.8 Gallon (22.0 L)  |
| Battery Charger                  | 48V DC, 120/230 VAC, UL & CSA   | N/A  |
| Speed Controller                 | 400 Amp   | N/A  |
| Drivetrain                       | Motor Shaft Direct Drive  | Continuously Variable Transmission (CVT)   |
| Transaxle                        | Differential with Helical Gears   | Differential with Helical Gears  |
| Gear Selection                   | Dash Mounted Forward-Neutral-Reverse  | Forward-Reverse  |
| Rear Axle Ratio                  | 14.7:1  | 11.42:1 (Forward) 15.78:1 (Reverse)  |
| PERFORMANCE                      |   | Thirties (Forward) 10.7 C.T (Hovoroo)  |
| Seating Capacity                 | 6-Passenger (4-Passenger with Optional Cargo Bed)   | 6-Passenger (4-Passenger with Optional Cargo Bed)  |
| Dry Weight (w/o batteries)       | 921 lb (418 kg)   | 992 lb (450 kg)  |
| Curb Weight                      | 1,417 lb (643 kg)   | 1,039 lb (471 kg)  |
| Vehicle Load Capacity            | 1,200 lb (544 kg)   | 1,200 lb (544 kg)  |
| Outside Clearance Circle         | 35.6 ft (10.9 m)  | 32.5 ft (9.9 m)  |
| Speed (level ground)             | 16.0 mph ± 0.5 mph (25.7 kph ± 0.8 kph)   | 16.0 mph $\pm$ 0.5 mph (25.7 kph $\pm$ 0.8 kph)  |
| STEERING & SUSPENSION            | 10.0 mpn ± 0.0 mpn (20.7 kpn ± 0.0 kpn)   | 10.0 прп ± 0.3 прп (23.7 крп ± 0.0 крп)  |
| Steering                         | Self-Compensating Rack and Pinion   | Self-Compensating Rack and Pinion  |
| Suspension                       | Leaf Springs with Hydraulic Shock Absorbers   | Leaf Springs with Hydraulic Shock Absorbers  |
| Service Brake                    | Rear Wheel Mechanical Self-Adjusting Drum   | Rear Wheel Mechanical Self-Adjusting Drum  |
| Parking Brake                    | Self-Compensating, Single Point Engagement  | Self-Compensating, Single Point Engagement   |
| Tires                            | Street Tires 18x10-10, Diamond Pattern Spoke Wheels   | Street Tires 18x10-10, Diamond Pattern Spoke Wheels  |
| BODY & CHASSIS                   | Street files fox to-to, Diamond Fattern Spoke Wheels  | Street files ToxTo-To, Diamond Pattern Spoke Wheels  |
| Frame                            | Welded Steel with DuraShield™ Powder Coat   | Welded Steel with DuraShield™ Powder Coat  |
| Body & Finish                    | Injection Molded TPO  | Injection Molded TPO   |
| Available Body Colors            | Almond, Black, Burgundy, Electric Blue, Flame Red, Forest<br>Green, Inferno Red, Ivory, Metallic Charcoal, Orange, Patriot<br>Blue, Platinum, White | Almond, Black, Burgundy, Electric Blue, Flame Red, Forest<br>Green, Inferno Red, Ivory, Metallic Charcoal, Orange, Patrio<br>Blue, Platinum, White, Yellow |
| Standard Seat Color              | Red on Black  | Red on Black   |
|                                  |   |  |



**FRONT** 



**BACK** 

## **POPULAR OPTIONS & ACCESSORIES**

- ► Fold-down windshield
- ▶ Roof
- ▶ Woodside stake cargo bed (replaces rear-facing seat)
- ▶ Roto-molded plastic cargo bed (replaces rear-facing seat)

  ▶ Comfort grip steering wheel
- ▶ High-output LED headlights
- ► Turn signals w/ 4-way flashers
- ► Hour meter
- ▶ Limited slip differential
   ▶ Clays Car<sup>TM</sup> field kit
- ► Locking glovebox doors
- ▶ Ashtray
- ▶ 12-volt accessory outlet (gas only)
- ► CE kit (gas only)
- ▶ Battery watering system (electric only)
   ▶ DC/DC converter (electric only)

